# >SPEAKERPHONE

Bluetooth Speakerphone for Teleconference

360° Omnidirectional Voice Pickup<sup>1</sup> Crystal Clear Sound Effect | Wireless Charging<sup>2</sup> 8-hour Playtime<sup>3</sup>

#### Omnidirectional Making Your Voice Heard

A CVTE Speakerphone supports 360-degree omnidirectional audio pickup to receive the voice from every seat in a meeting room.

6-Element

 360°
 5 Meters<sup>4</sup>

 Omnidirectional
 Voice Pickup Radius





## **Crystal Clear Calls**

PZM | High Performance Structure Design Speaker Acoustic Echo Cancellation | Noise Reduction

#### Set up in Seconds

Seamless Connection Connect via Bluetooth, a USB cable or an audio cable<sup>5</sup> Plug and Play Instantly operational after connection

Multiple Devices Connection Connects up to 3 devices at the same time

## Wired & Wireless Charging

Supports 8-hour of Playtime on a single charge

8 Hours Durable battery life

USB Cable & Charging Pad Either way, charing could be easy

	Dreduct Cresting
Product Specification	
Microphone	
Pickup Distance	5 Meters Radius
Microphone	6-Eement Microphone Array
Frequency	150Hz~8kHz
Sensitivity	-38dBV
Signal to Noise Ratio	65dB
Speaker	
Maximum Sound Pressure Level	80dB SPL@1m
Distortion	≦4% @150Hz~16kHz
Signal-to-noise Ratio	≥75dB@1m
Frequency Response	150Hz~16kHz
I/O Ports & Buttons & Indicators	
Dort	USB Type C (Audio in/out + Charge 5V/2A)
Port	AUX 3.5mm (Audio in/out)
Bluetooth	BT4.2+EDR
Mode	Music mode/Call mode (in Bluetooth mode)
Buttons	6 (Power, Answer/hang up, Mute, Bluetooth, Volume+, Volume-)
Indicator Light	Power, Volume, Blutooth, Mute, Answer/Hang up
Physical Specification	
Dimension (Diameter×Height)	120mm×35.2mm
Net Weight	395g
Color	Dark Gray
Battery	
Battery Capacity	7.4V/2200mAh
Charaina Dequirement	Wired 5V/2A
Charging Requirement	Wireless 5W
Battery Life on a Single Charge	Up to 8 hours
Environment	
Operating Temperature	-5℃~40℃
Operating Humidity	10%~90%RH
Storage Temperature	-20℃~60℃
Storage Humidity	10%~90%RH
Operating Altitude	Below 5000 meters

\* All data from CVTE Lab.